





All-metal body
Stable operation
Aluminium alloy blade, low noise
Can be connected to air ducts
Easy to move, convenient to use.



PVT-20, PVT-25, PVT-30



PVT-35, PVT-40



PVT-45, PVT-50, PVT-60



Specifications:

Model	Size	Voltage & Frequency	Power (W)	Speed RPM	Air Volume		Pressure (Pa)	Noise dB(A)	Outline dimensions						
					(m³/h)	CFM			D	D1	D2	W	W1	W2	H
PVT-20/8"	200	220-240V~50/60Hz	180	3200	1300	764	200	65	200	226	250	300	210	210	295
PVT-25/10"	250		280	3200	2000	1176	250	70	240	266	290	300	210	252	335
PVT-30/12"	300		550	3200	3400	2000	350	80	300	326	350	325	230	256	400
PVT-35/14"	350		1200	3200	5100	3000	440	85	350	384	400	380	260	375	434
PVT-40/16"	400		1600	3200	7700	4530	520	90	400	434	450	400	285	412	484
PVT-45/18"	450		1800	3200	10000	5882	660	95	450	484	500	450	335	462	534
PVT-50/20"	500		2200	3200	12000	7059	800	100	496	534	550	450	335	512	584
PVT-60/24"	600		2200	1660	13500	7941	350	85	600	634	655	450	335	612	684